

MOVING YOU FURTHER

HX300S

L



MOVING YOU FURTHER

HX300S

L

Specification



*Photo may include optional equipment.

Gross Power
194 kW (260 HP) at 2,200 rpm

Net Power
190 kW (255 HP) at 2,200 rpm

Bucket Capacity
1.27 m³ (1.66 yd³)

Operating Weight
30,200 kg / 66,580 lb



ENGINE	STD	OPT
Hyundai HM8.3 Engine	☒	
HYDRAULIC SYSTEM	STD	OPT
Intelligent Power Control (IPC)		
3-power mode, 2-work mode, user mode	☒	
Variable power control	☒	
Pump flow control	☒	
Attachment mode flow control		☒
Engine auto idle	☒	
Engine auto shutdown control		☒
CAB & INTERIOR	STD	OPT
ISO Standard Cabin		
Rise-up type windshield wiper	☒	
Radio / USB player	☒	
Handsfree mobile phone system with USB	☒	
12 V power outlet (24 V DC to 12 V DC converter)	☒	
Electric horn	☒	
All-weather steel cab with 360° visibility	☒	
Safety glass windows	☒	
Sliding fold-in front window	☒	
Sliding side window (LH)	☒	
Lockable door	☒	
Hot & Cool box	☒	
Storage compartment & Ashtray	☒	
Sun visor	☒	
Door and cab locks, one key	☒	
Pilot-operated slidable joystick	☒	
Cabin lights		☒
Cabin front window rain guard		☒
Cabin roof-steel cover	☒	
Automatic Climate Control		
Air conditioner & Heater	☒	
Defroster	☒	
Starting aid (air grid heater) for cold weather	☒	
Centralized Monitoring		
8" LCD display - Normal type	☒	
8" LCD display - Premium type		☒
Engine speed or trip meter / Accel	☒	
Engine coolant temperature gauge	☒	
Max power	☒	
Low speed / High speed	☒	
Auto idle	☒	
Overload warning with alarm		☒
Check engine	☒	
Air cleaner clogging	☒	
Indicators	☒	
ECO gauges	☒	
Fuel level gauge	☒	
Hyd. oil temperature gauge	☒	
Warnings	☒	
Communication error	☒	
Low battery	☒	
Clock	☒	
Seat		
Mechanical suspension without heater	☒	
Mechanical suspension with heater		☒
Adjustable air suspension without heater		☒
Adjustable air suspension with heater		☒
Cabin FOPS/FOG		
FOPS (Falling object protective structures) ISO 10262 Level 2		☒
FOG (Falling object guard) ISO/DIS 10262 Level 2	Front & Tops guard	☒
	Top guard	☒
Cabin ROPS		
ROPS (Roll over protective structures)ISO 12117-2		☒

SAFETY	STD	OPT
Battery master switch	☒	
Rearview camera		☒
AAVM (Advanced around view monitoring)		☒
Four front working lights (2 boom mounted, 2 front frame mounted)	☒	
Travel alarm	☒	
Rear work lamp		☒
Beacon lamp		☒
Automatic swing brake	☒	
Boom holding system	☒	
Arm holding system	☒	
Safety lock valve for boom cylinder with overload warning device		☒
Safety lock valve for arm cylinder		☒
Swing Lock system		☒
Two outside rearview mirror	☒	
ATTACHMENT	STD	OPT
Booms		
6.25 m, 20' 6" Mono	☒	
10.20 m, 33' 6" Long Reach		☒
Arms		
2.10 m, 6' 11"		☒
2.5 m, 8' 2"		☒
3.05 m, 10' 0"	☒	
3.75 m, 12' 4"		☒
7.85 m, 25' 9" Long Reach		☒
OTHERS	STD	OPT
Removable clean-out dust net for cooler	☒	
Removable washer tank	☒	
Fuel pre-filter	☒	
Fuel warmer		☒
Self-diagnostics system	☒	
Hi MATE (Remote management system)		☒
Batteries (2 × 12 V × 150 AH)	☒	
Fuel filler pump (50 lpm)		☒
Single-acting piping kit (Breaker, etc.)		☒
Double-acting piping kit (Clamshell, etc.)		☒
Rotating piping kit		☒
Quick coupler piping		☒
Quick coupler		☒
Accumulator for lowering work equipment	☒	
Pattern change valve (4 patterns)		☒
Fine swing control system		☒
General type guardrail		☒
Tool kit		☒
UNDERCARRIAGE	STD	OPT
Lower frame under cover (Additional)		☒
Lower frame under cover (Normal)	☒	
Track Shoes		
Double grouser shoe (700 mm, 28")		☒
Triple grouser shoe (600 mm, 24")	☒	
Triple grouser shoe (700 mm, 28")		☒
Triple grouser shoe (800 mm, 32")		☒

* Standard and optional equipment may vary. Contact your hyundai dealer for more information.
 The machine may vary according to international standards.
 * The photos may include attachments and optional equipment that are not available in your area.
 * Materials and specifications are subject to change without advance notice.
 * All imperial measurements rounded off to the nearest pound or inch.